

Univers

Lunia L Product Specifications



Published: January 2022





















Lunia L

Big dreams, big freedom – our new Lunia makes climbing wishes come true. It is available in three different sizes, from 9 metres to a height of almost 12 metres. The spatial net inside can be reached via different ascent possibilities, such as Climbing Plates or Rope Ladders. For even more fun in the three-dimensional climbing net, Flubber or Pendulum Seats can be added. Despite the large play volume, the play structure has a small foot print.

The textile membrane is dirt-repellent, 100 % recyclable and resistant to UV light. In addition, it protects the little climbers from the sun. Lunia can be used as a hot air balloon with basket or without a basket with the design of your choice. The membrane of the balloon is protected from vandalism by a safety grid surrounding the three-dimensional netting.



90.137.001

 Product Family	Univers
 Length x Width x Height (m)	5,7 × 5,7 × 10,0
 Length x Width x Height (ft)	18-6 × 18-6 × 32-9
 Protective Surfacing Area acc. to DIN EN 1176 (m)	7,9 × 7,9
 Protective Surfacing Area acc. to ASTM/CSA (m)	6,7 × 6,7
 Protective Surfacing Area acc. to ASTM/CSA (ft)	21-10 × 21-10
 Fall Height acc. to EN 1176 (m)	2,89
 Fall Height acc. to ASTM/CSA (ft)	9-6
 Age	5
 Minimum Space required acc. to DIN EN 1176 (m ²)	48,2
 Minimum Space required acc. to ASTM 1487 (ft ²)	374,4
 Number of Foundations	1
 Concrete Volume C20/C25 (m ³)*	3,9*
 Number of skilled Installers required	4
 Installation Time without Foundation	26 hours
 Dimensions of largest Part (m)	0,6 × 0,6 × 6,7
 Weight of heaviest Part (kg)	900
 Shipping Volume (m ³)	On request
 Total Weight (kg)	On request
 Spare Part Guarantee	Lifelong

The dimensions of the equipment and protective surfacing area have been rounded up to one decimal digit.

* The foundation size refers to a project in wind zone 3 according to EN 1991-1-4.

Technical Data

Technical changes are reserved. The following text can also be used for tenders.

Central Mast:

A steel post with a diameter of Ø 273 mm (10 3/4") and a wall thickness of 20 mm (13/16").

Tubes:

A combination of Frameworx® steel tubes with diameters of Ø 60.3 mm (2 3/8"), Ø 48.3 mm (1 7/8") and Ø 26.9 mm (1 1/16") are used in the entrance area, ascent and balloon.

Support Structure:

Hollow steel profiles measuring 80 x 80 mm (3 1/8" x 3 1/8") and steel sheets with a thickness of 10 mm (3/8") form the support structure.


Balloon Rings:

The three balloon rings for tensioning the membrane are made of stainless-steel tubing with diameters of Ø 60.3 mm (Ø 2 3/8") and Ø 48.3 (Ø 1 7/8").

Balls:

The Frameworx®-aluminium ball connectors with a diameter of Ø 250 mm (9 13/16") are in combination with spatial nets equipped with the internal, patented AstemTT® tensioning system. They are all securely closed with durable EPDM caps.

The mast, tubes, support structure and balls are colour powder-coated in a solvent-free epoxy-polyester stoving process and partially thermally galvanised.



Ropes:

U-Rope®-round strand ropes with galvanised steel cores and diameters of Ø 16 mm (5/8"), Ø 18 mm (13/16"), and Ø 20 mm (13/16"). The external strands are covered with high abrasion-resistant and UV-resistant polyester-yarn (no Polypropylene).

Spatial Net:

The net structures are fixed at the rope crossing points by durable aluminium parts such as cloverleaf ring, forged ball knot, T-connectors and barrel-ferrule (no plastic). Spatial nets are low in follow-up costs due to individually replaceable rope strands.

Planar Nets:

The narrow- and wide-mesh planar nets are permanently fixed at the rope crossing points by durable, drop-forged aluminium ball knots (no plastic) and fastened to the main structure with aluminium pipe clamps.

HPL:

HPL panels with a thickness of 18 mm (11/16") and anti-slip surface are used in the access and ascent areas. They are attached with aluminium panel clamps.



Safety Nets & Grid Frames:

The stainless-steel safety nets in the access area are made of steel cable with \varnothing 1.5 mm ($\frac{1}{16}$ ") and mesh size of 40 x 75 mm ($1 \frac{1}{4}$ " x $2 \frac{3}{4}$ "). They are connected to the corresponding tubes by wrapping. The stainless-steel wire of the mesh frames in the balloon area has a thickness of 4 mm ($\frac{3}{16}$ ") and mesh size of 40 x 40 mm ($1 \frac{1}{4}$ " x $1 \frac{1}{4}$ "). They are fixed with cast aluminium pipe clamps.

GRP Rods:

Round rods made of glass-fibre reinforced plastic are used to brace the balloon skin. The diameter is \varnothing 16 mm ($\frac{5}{8}$ ").

Textile Membrane:

UV light and wind load resistant membrane fabric made of high technology mesh fabric – printable, stain resistant and recyclable.

Rope Ladder:

Ropes with a diameter of \varnothing 16 mm ($\frac{5}{8}$ ") and black rungs made of durable polyamide round material with \varnothing 40 mm ($1 \frac{1}{4}$ ").

Climbing Rope:

Rope with a diameter of \varnothing 18 mm ($\frac{3}{4}$ ") is equipped with climbing knots made of durable hard rubber (not plastic). These are fixed with aluminium press clamps.