

Published: June 2022

Wonderwalls.01

Fitted with a wealth of play functions in a reduced space Wonderwalls are specifically aimed at the needs of toddlers and pre-school children. Each equipment design offers a number of play worlds that are interconnected by windows and passages between the three or respectively four walls, which are fanned out around a central post.

As well as space for retreat, children are encouraged to engage in role-playing games using elements such as mud tables, benches, sand workshops or openings in the walls. Language and social skills are fostered and trained in a playful way.

The highlight of Wonderwalls.01 in the design of a tree stump is a passage with rubber membranes connecting two play areas. And anyone looking closely will find a secret opening under the bench.

Wonderwalls.01

Published: June 2022

90.295.700.1 Product Family **Spooky Rookies** Length x Width x Height (m) 2,3 x 2,7 x 1,7 Length x Width x Height ('-") 7-7 x 8-11 x 5-4 Protective Surfacing Area acc. to DIN EN 1176 (m) 5,3 x 5,7 Protective Surfacing Area acc. to ASTM/CSA (m) 6,0 x 6,4 Protective Surfacing Area acc. to ASTM/CSA ('-'') 19-7 x 20-11 Fall Height acc. to EN 1176 (m) 1,21 Fall Height acc. to ASTM/CSA ('-") 4-0 3 Minimum Space required acc. to DIN EN 1176 (m²) 20.95 Minimum Space required acc. to ASTM 1487 (ft²) 287,8 Number of Foundations Concrete Volume C20/C25 (m³) 0,63 Number of skilled Installers required Installation Time without Foundation 8 hours Dimensions of largest Part (m) 1,5 x 1,2 Weight of heaviest Part (kg) 40 Shipping Volume (m³) On request Total Weight (kg) On request Spare Part Guarantee Lifelong



Technical Data

Technical changes are reserved. The following text can also be used for tenders.


Included Products:

- Rubber Membrane Curtain
- Puzzle Elements
- Mud Tables
- Rotating Disc

Tubes:

The Steel tubes with a diameter of \emptyset 60,3 mm (2 %") and a wall thickness of 2,9 mm (%") are thermally galvanised to protect against corrosion and powder-coated in colour using a solvent-free epoxy/polyester/process. They are also watertight closed with rounded aluminium caps.





HDPE-Panels:

Wall, play and design elements are made of solid-coloured and grained HDPE panels with a thickness of 19 mm (34'') and form milled. All edges are rounded off and the walls are connected to the pipes with cast aluminium panel clamps.

Rubber Membrane:

The rubber mat strips are made of durable and vandal-proof conveyor belt.