


## CatTail.01 – Product Specification



### Cat Tail.01

The full-size Cat Tail.01 sways to and fro all the time... hey, it's a cat tail!

The Cat Tail has a body and a stem made out of stainless steel. The curved stem and the bi-colored HDPE-platform turns a piece of play equipment into an eye-catcher for all public places in town.



### Cat Tail.01 – at a glance.

Product Family:	<b>Playpoints</b>	Number of Foundations:	<b>1 pc.</b>
Item Number:	<b>90.260.201</b>	Concrete Volume C20/C25:	<b>0.5 m<sup>3</sup> (18 ft<sup>3</sup>)</b>
Children's Age:	<b>5+</b>	Number of skilled installers required:	<b>2</b>
Fall Height (DIN EN 1176):	<b>0.4 m (1'-4")</b>	Installation Time without foundation:	<b>2 hours</b>
Length x Width x Height:	<b>0.7 m x 0.4 m x 2.5 m</b> <b>(2'-4" x 1'-4" x 8'-3")</b>	Dimensions of largest part:	<b>0.7 m x 0.4 m x 2.9 m</b> <b>(2'-4" x 1'-4" x 9'-7")</b>
Protective Surfacing Area (DIN EN 1176):	<b>3.6 m x 3.6 m</b>	Weight of the heaviest part:	<b>55 kg (122 lbs)</b>
Protective Surfacing Area (ASTM 1487):	<b>4.3 m x 4.3 m</b> <b>(14'-2" x 14'-2")</b>	Shipping Volume:	<b>1.7 m<sup>3</sup> (60.1 ft<sup>3</sup>)</b>
Minimum space required DIN EN 1176:	<b>10.2 m<sup>2</sup></b>	Shipping Weight:	<b>85 kg (188 lbs)</b>
Minimum space required ASTM 1487:	<b>14.3 m<sup>2</sup> (154 ft<sup>2</sup>)</b>	Spare part guarantee:	<b>Lifelong</b>
		Certificate according to DIN EN 1176:	<b>No.: Z2 15 07 10256 237</b> <b>TÜV Product Service</b>

### Technical Data.

The following text can also be used for tenders.

## CatTail.01 – Product Specification

### Base plate:

Stainless steel plate Ø 320 mm (1'-1"), covered with HDPE panels, 19 mm (3/4") thickness

### Tubes:

Stainless steel tubes, Ø 48.3 & 40,0 mm (1'-7" & 1'-4"), slightly bended, connected to an Frameworkx®-aluminum ball connector; Ø 200 mm (8"); anti-corrosion treatment and color finish: sandblasting and solvent-free zinc-/ epoxy-/ polyester-process; securely closed with durable EPDM-cap

# URBAN DESIGN

### Luffing mechanism:

Fully encapsulated rubber-metal-bearing integrated in stainless steel foundation tube

### Covering:

Antiskid HDPE panels, 19 mm (3/4"), bolted on the base plate

