
CatTail.02 – Product Specification

RBAN DESIGN





The full-The medium Cat Tail complements the range with a version for mediumsized players. It looks even more attractive when grouped in an arrangement with one or more of the other available sizes of the Cat Tail.





Cat Tail.02 - at a glance.

Product Family: Item Number: Children's Age: Fall Height (DIN EN 1176): Length x Width x Height:

Protective Surfacing Area (DIN EN 1176): Protective Surfacing Area (ASTM 1487):

Minimum space required DIN EN 1176: Minimum space required ASTM 1487:

Playpoints 90.260.202

0.4 m (1'-4")

 $0.7 \,\mathrm{m} \times 0.4 \,\mathrm{m} \times 2.1 \,\mathrm{m}$ (2'-4" x 1'-4" x 6'-11")

3.6 m x 3.6 m 4.3 m x 4.3 m (14'-2" x 14'-2")

10.2 m²

14.3 m² (154 ft²)

Number of Foundations: Concrete Volume C20/C25: Number of skilled installers required: Installation Time without foundation:

Weight of the heaviest part: Shipping Volume: **Shipping Weight:** Spare part quarantee:

Dimensions of largest part:

Certificate according to DIN EN 1176:

1 pc. 0.5 m3 (18 ft3)

2 hours

0.7 m x 0.4 m x 2.5 m (2'-4" x 1'-4" x 8'-3")

50 kg (111 lbs) 1.5 m³ (53 ft³) 80 kg (177 lbs) Lifelong

No.: Z2 15 07 10256 237 **TÜV Product Service**

Technical Data.

The following text can also be used for tenders.

Base plate:

Stainless steel plate Ø 320 mm (1'-1"), covered with HDPE panels, 19 mm (3/4") thickness

Tubes:

Stainless steel tubes, Ø 48.3 & 40,0 mm (1'-7" & 1'-4"), slightly bended, connected to an Frameworx®-aluminum ball connector; Ø 200 mm (8"); anti-corrosion treatment and color finish: sandblasting and solvent-free zinc-/ epoxy-/ polyesterprocess; securely closed with durable EPDM-cap

Luffing mechanism:

Fully encapsulated rubber-metal-bearing integrated in stainless steel foundation tube

Covering:

Antiskid HDPE panels, 19 mm (3/4"), bolted on the base plate



