

Swingo.2.2 – Product Specification

BAN DESIG





Swingo.2.2 The two-bay-version of the smaller Swingos is asymmetrical. That looks cool and it doesn't keep the two users from going to and fro in harmony.





Swingo.2.2 - at a glance.

Product Family: Item Number: Children's Age: Fall Height (DIN EN 1176): Length x Width x Height:

Protective Surfacing Area (DIN EN 1176): Protective Surfacing Area (ASTM 1487):

Minimum space required DIN EN 1176: Minimum space required ASTM 1487:

Playpoints 90.260.502 3+

1.3 m (4'-4") $3.8 \, \text{m} \times 1.7 \, \text{m} \times 2.5 \, \text{m}$ (12'-6" x 5'-7" x 8'-3")

7.2 m x 3.8 m 8.0 m x 7.5 m (26'-3" x 24'-8")

27.0 m²

46.5 m² (501 ft²)

Number of Foundations: Concrete Volume C20/C25: Number of skilled installers required:

Installation Time without foundation: Dimensions of largest part:

Weight of the heaviest part: Shipping Volume: Shipping Weight:

Spare part guarantee: Certificate according to DIN EN 1176: 4 pc.

0.6 m3 (21.2 ft3) 2

2 hours 3.2 m x 0.6 m x 0.1 m

(10'-6" x 2'-0" x 0'-4") 35 kg (78 lbs) 1.5 m³ (53 ft³) 160 kg (353 lbs) Lifelong

No.: Z2 15 06 10256 231 **TÜV Product Service**

Technical Data.

The following text can also be used for tenders.

Framework:

Stainless steel tube bends Ø 60.3 mm (2 3/8"), connected to Frameworx®-aluminum ball connectors; Ø 250 mm (9-13/16"); anti-corrosion treatment and color finish: sandblasting and solvent-free zinc-/ epoxy-/ polyester-process; securely closed with durable EPDM-caps

The black rubber safety swing seat is by stainless steel chains rotatable mounted to the cross tube mounted in maintenance free nylon bushes

