
Swingo.2.4 – Product Specification







Swingo.2.4

The large two-bay-version of the Swingo combines asymmetry and high-flying-dynamics.

Cool game - cool look!

Swingo.2.4 - at a glance.

Product Family: Item Number: Children's Age: Fall Height (DIN EN 1176): Length x Width x Height:

Protective Surfacing Area (DIN EN 1176): Protective Surfacing Area (ASTM 1487):

Minimum space required DIN EN 1176: Minimum space required ASTM 1487:

Playpoints 90.260.504 3+

1.7 m (5'-7") 5.9 m x 2.5 m x 3.4 m (19'-5" x 8'-3" x 11'-2")

8.9 m x 3.7 m 11.6 m x 9.6 m

(38'-1" x 31'-6")

32.2 m²

66.9 m² (721 ft²)

Number of Foundations: Concrete Volume C20/C25: Number of skilled installers required:

Installation Time without foundation: Dimensions of largest part:

Weight of the heaviest part: Shipping Volume:

Shipping Weight: Spare part guarantee:

Certificate according to DIN EN 1176:

6 pc. 0.9 m³ (32 ft³)

2 hours

 $3.8 \, \text{m} \, \text{x} \, 1.2 \, \text{m} \, \text{x} \, 0.1 \, \text{m}$ (12'-6" x 4'-0" x 0'-4")

35 kg (78 lbs)

1.7 m³ (61 ft³) 185 kg (408 lbs)

Lifelong

No.: Z2 15 06 10256 231 **TÜV Product Service**

Technical Data.

The following text can also be used for tenders.

Framework:

Stainless steel tube bends Ø 60.3 mm (2 3/8"), connected to Frameworx®-aluminum ball connectors; Ø 250 mm (9-13/16"); anti-corrosion treatment and color finish: sandblasting and solvent-free zinc-/ epoxy-/ polyester-process; securely closed with durable EPDM-caps

Swing seat:

The black rubber safety swing seat is by stainless steel chains rotatable mounted to the cross tube mounted in maintenance free nylon bushes



